

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listings of claims in the above-identified application.

**Listing of Claims:**

1-2. (Canceled)

3. (Previously presented) A method for alerting e-mail users comprising:

if a failed delivery e-mail message is received, setting an indicator in an entry in one of an address book, an address database, and an address cache associated with an address of an addressee corresponding to the failed delivery message;

displaying said address in conjunction with a perceptive cue in response to said indicator being set;

wherein, if said indicator is set, said indicator is operable for clearing in response to said address becoming accessible; and

clearing said indicator in response to subsequently receiving an e-mail originated from the address of the addressee corresponding to the failed delivery message.

4-9. (Canceled)

10. (Currently amended) A computer program product embodied in a ~~tangible~~ non-transitory storage medium, the program product for alerting e-mail users comprising programming instructions for:

if a failed delivery e-mail message is received, setting an indicator in an entry in one of an address book, an address database, and an address cache associated with an address of an addressee corresponding to the failed delivery message;

displaying said address in conjunction with a perceptive cue in response to said indicator being set;

wherein, if said indicator is set, said indicator is operable for clearing in response to said address becoming accessible; and

programming instructions for clearing said indicator in response to subsequently receiving an e-mail originated from the address of the addressee corresponding to the failed delivery message.

11-16. (Canceled)

17. (Previously presented) A data processing system comprising:
- circuitry operable for, if a failed delivery message is received, setting an indicator in an entry in one of an address book, an address database, and an address cache associated with an address of an addressee corresponding to the failed delivery message;
  - circuitry operable for displaying said address in conjunction with a perceptive cue in response to said indicator being set;
  - wherein, if said indicator is set, said indicator is operable for clearing in response to said address becoming accessible; and
  - circuitry operable for clearing said indicator in response to subsequently receiving an e-mail originated from the address of the addressee corresponding to the failed delivery message.

18-20. (Canceled)